

FUSO – A Daimler Group Brand



2017

# FE160

Efficiency that delivers.



MITSUBISHI FUSO TRUCK OF AMERICA, INC.

# FE160

## SPECIFICATIONS

A true workhorse, the FUSO FE160 will change the way you think about keeping your business moving. Featuring an innovative two-stage turbocharged, low-emissions diesel engine and dual-clutch automatic transmission, you'll benefit from increased fuel savings, enhanced efficiencies, higher payload capacity, and improved driver productivity. Add to this our 5-year/175,000-mile powertrain limited warranty and you get the longevity and durability you can expect from FUSO.



WEIGHT RATINGS	GVWR/GCWR	15,995 lb./23,710 lb.				
	GAWR (front/rear)	6,390 lb./12,700 lb.				
CURB WEIGHT	Base model	5,505 lb. (est.)				
BODY/PAYLOAD	Estimated max.	10,490 lb. (see dealer for details)				
DIMENSIONS	Wheelbase	110.2" (C)	133.9" (E)	151.6" (G)	169.3" (H)	187.0" (K)
	Overall length (cab/chassis)	204.9"	228.5"	246.3"	264.0"	281.7"
	Usable cab to rear axle	81.2"	104.9"	122.6"	140.3"	158.0"
	Body sizes accommodated	10' to 20' (22' with FUSO review/approval)				
ENGINE	Model	FUSO 4P10-T5 Diesel				
	Type	DOHC, 4-cylinder, 4-stroke cycle, water-cooled, turbocharged, intercooled diesel with 4 valves per cylinder, with high-efficiency electrically-engaged cooling fan				
	Displacement/Emissions	183 cu. in. (3.0 L) Electronically controlled DPF/SCR system with OBD				
	Max. output (SAE, gross)	161 hp @ 3,400 rpm				
	Max. torque (SAE, gross)	295 lb.-ft. @ 1,300 rpm				
AIR CLEANER	Type	Dry paper element with snorkel				
TRANSMISSION	Standard equipment	M038S6 DUONIC® 6-speed dual-clutch automatic				
AXLE CAPACITY	Front/Rear	6,835 lb./13,230 lb.				
	FINAL REDUCTION GEAR	Type	Single-reduction hypoid			
TOP SPEED, EST.	Ratio (std./opt.)	5.285/5.714				
	Std. diff./Opt. diff.	83/76 mph				
TURNING DIAMETER	Minimum, by wheelbase	34.1'	40.0'	44.6'	49.5'	54.1'
TIRES (PREMIUM)	Configuration	Single front, dual rear				
	Size/Type	215/75R17.5 12PR LR:F hwy front/traction rear				
WHEELS	Size/Configuration	17.5" x 6"/6-lug				
STEERING	Type	Ball-nut type with integral-type hydraulic power boost				
	Adjustments	Tilt/telescoping steering column with steering lock				
SUSPENSION	Front	Laminated leaf springs with shock absorbers and stabilizer bar				
	Rear	Laminated leaf springs with shock absorbers and stabilizer bar				
BRAKES	Service	Dual-caliper discs, vacuum/hydraulic-type with ABS				
	Parking	Drum/driveline, internal expanding shoe				
	Exhaust	Electrically actuated				
FRAME	Type	Ladder/straight				
	Section modulus	7.08 cu. in. per rail				
	Yield strength	56,565 psi				
	RBM per rail	400,410 lb.-in.				
	Height/Width	32.8"/33.5"				
	Environmental durability	Premium anti-corrosion package for frame and frame-mounted components				
FUEL TANK	Capacity/Location—std.*	30 gal./in-frame, aft of rear axle				
	Capacity/Location—opt.**	33 gal./left side				
DEF TANK	Capacity/Location	3.2 gal./right side				
BATTERY	Type/Capacity	Two 12-volt, maintenance-free/750 CCA				
ELECTRICAL	Starter/Alternator	12-volt/12-volt, 140A output				
COLD WEATHER	Starting/Operation	Ceramic glow plugs/PCV heater, DEF tank heater				
CONVENIENCE/ASSURANCE	Windows/Door locks	Power-operated, one-touch up and down driver's side window				
	Cruise control	Standard (programmable)				
	Entry	Keyless, with driver/assistant door lock control				
	Radio	Clarion AM/FM/CD, hands-free Bluetooth® (optional)				
	Air conditioning	Standard factory-installed				
	Idle Limit System (ILS)—opt.	Automatic engine shutdown of stationary vehicle, in Park or Neutral, after achieving normal operating temperature with dealer-programmed limit of 3, 5, or 10 minutes				
	Collision avoidance system	Mobileye® 6 Series (optional)				

## KEY BENEFITS

- Comfortable for any driver, the FE160 serves well in construction, landscaping, and transport industries
- Our exclusive DUONIC® dual-clutch automatic transmission offers effortless navigation of city streets and heavy traffic
- Enjoy the long haul in our most comfortable cab ever, fully equipped with an ergonomically designed interior, adjustable steering wheel, and spacious seating and stowage
- From sunrise to sundown, a panoramic windshield and a driver-to-ground line of sight of only 6 ft. ensure you stay focused on what's ahead
- Go further on less with our ultra-efficient advanced dual-turbo diesel engine with access to high torque whenever it's needed
- Mobileye® system provides audible and visual alerts for speeding, lane departure, potential pedestrian or vehicle collisions


\*Optional feature

## CAB COLORS

ARCADIA SILVER	MARS RED
NATURAL WHITE	SHANNON BLUE
JUPITER GREEN	SOLID BLACK

All models are available immediately in white. Other colors shown (except Solid Black) may be special-ordered at no extra charge. Accuracy of indicated hues is limited by paper/electronic reproduction.

## FABRIC STYLE



Vehicle specifications are subject to change without notice. Photos and descriptions included in this spec sheet may vary in comparison to actual vehicle models. Please see your local dealer for details and warranty limitations.

\*rear fuel tank is not designed for use as a primary or auxiliary in any dual tank system

\*\*133.9", 151.6", 169.3", 187.0" wb

PRINTED IN THE U.S.A.

©2017 MITSUBISHI FUSO TRUCK OF AMERICA, INC.

**MITSUBISHI FUSO TRUCK OF AMERICA, INC.**

2015 Center Square Road  
Logan Township, NJ 08085

[MITFUSO.COM](http://MITFUSO.COM)

