

# MOVING YOUR BUSINESS FORWARD.

FUSO FE GAS TRUCK



## **SPECIFICATIONS THAT GET DOWN TO BUSINESS.**

	FE <b>140</b> GAS	FE <b>160</b> GAS
MODEL YEAR AVAILABLE	2020 and 2019	2020 and 2019
CAB CONFIGURATION	SINGLE	SINGLE & CREW
EHICLE WEIGHT CLASS	4	4
/EIGHT RATINGS		
VWR/GCWR - pounds	14,500 / 22,215	15,995 / 23,710
AWR (front/rear) - pounds	6,390 / 12,700	6,390 / 12,700
ODY / PAYLOAD CAPACITY		
faximum (estimated) - pounds	8,800	10,295 (single) 9,715 (crew)
IMENSIONS		
/heelbase	133.9" (E) 151.6" (G) 169.3" (H) 187.0" (K)	133.9" (E) 151.6" (G) 169.3" (H) 187.0" (K)
verall length (cab/chassis)	228.5" 246.3" 264.0" 281.7"	228.5" 246.3" 264.0" 281.7"
verall height, est.	89.0"	89.0" (single) 91.5" (crew)
verall width (not including mirrors)	84.4"	84.4"
sable cab to rear axle	104.9" 122.6" 140.3" 158.0"	104.9" 122.6" 140.3" 158.0" (single) 103.4" 121.1" (crew
ody sizes accommodated	12' to 20' (22' with FUSO review)	12' to 20' (22' with FUSO review)(single)
200, 0.200 a000mmodatod	12 to 20 (22 marr 500 to to to to)	12' to 18' (19' with FUSO review) (crew)
NGINE		(, (,
lodel	FUSO PSI-GMPT, V8, 6.0L gasoline	FUSO PSI-GMPT, V8, 6.0L gasoline
/ре	Gasoline	Gasoline
splacement	6.0L (365 in <sup>3</sup> )	6.0L (365 in³)
igine power - hp	297	297
igine power - rip ngine torque - Ib-ft	361	361
• .		
ruise control	Standard  CNC and LRC capable in future models (entire)	Standard  CNC and LPC canable in future models (entire)
Iternative fuels	CNG and LPG capable in future models (option)	CNG and LPG capable in future models (option)
UEL TANK	40 (la sell off aut	40 / le seil eft eut
apacity - gallons/location	40 / In-rail aft-axle	40 / In-rail aft-axle
RANSMISSION	AW 4000 0 1 =:	AIII 4000 0 / =:
rand & model	Allison 1000 Series™	Allison 1000 Series™
ype	6-speed automatic, torque converter with lockup clutch	6-speed automatic, torque converter with lockup clutch
ontrol system	Electronic, closed-loop with adaptive shift mapping	Electronic, closed-loop with adaptive shift mapping
TO provision	Torque converter turbine-driven spur gear (option)	Torque converter turbine-driven spur gear (option)
hift selector	Dash-mounted	Dash-mounted
uelSense <sup>®</sup> 2.0, with DynActive™	Standard	Standard
RAME		
уре	C-channel, straight	C-channel, straight
ection modulus, per rail - in <sup>3</sup>	7.08	7.08
ield strength - psi	56,565	56,565
esistance bending moment, per rail - lb-in	400,410	400,410
eight/width - inches	32.8 / 33.5	32.8 / 33.5
owder-coated frame	Standard	Standard
remium anti-corrosion package*	Standard	Standard
XLE DATA	Ottalidard	Standard
atings (front/rear) - pounds	6,835 / 13,230	6,835 / 13,230
/pe (rear)	Single-reduction hypoid	Single-reduction hypoid
atio (rear)	5.285	5.285
mited slip differential	Option	Uption
USPENSION		
/pe (front & rear)	Laminated leaf springs	Laminated leaf springs
IRES & WHEELS		
onfiguration	Single front, dual rear	Single front, dual rear
ire size/type	215/75R17.5 12PR LR:F hwy front / traction rear	215/75R17.5 12PR LR:F hwy front / traction rear
/heel size - inches/type	17.5" x 6" /6-lug	17.5" x 6" /6-lug
RAKES		
ervice	Dual-caliper discs, vacuum/hydraulic	Dual-caliper discs, vacuum/hydraulic
arking	Drum/driveline, internal expanding shoe	Drum/driveline, internal expanding shoe
BS system	4-channel	4-channel
TEERING		
/pe	Integral hydraulic boost	Integral hydraulic boost
olumn adjustment	Tilt & telescoping	Tilt & telescoping
urning diameter (min. by WB) - feet	40.1, 44.8, 49.5, 54.2	40.1, 44.8, 49.5, 54.2 (single) 49.5, 54.2 (crew)
LECTRICAL	, 1110, 1010, 0 112	. 5.1, 1.10, 1010, 5.12 (billing)
attery	Maintenance-free / 1125 CCA	Maintenance-free / 1125 CCA
ternator - amps	180	180
VTERTAINMENT	100	100
	Ontion	Ontion
M/FM/CD/USB, hands-free Bluetooth® radio	Option	Option
AFETY & CONVENIENCE		2: 1 1
alogen headlamps	Standard	Standard
aytime running lights	Standard	Standard
ront power-operated**, One-touch up/down windows***	Standard	Standard
eyless entry	Standard	Standard
USO red high visibility seat belts	Standard	Standard
030 fed flight visibility seat belts	o tarraara	

Your business deserves a truck tailored to its unique needs. That's why FUSO FE GAS trucks give you a broad range of specs and features to choose from. Available in various sizes and a range of interior trims, you'll find all the options you could ask for. Your local dealer will guide you in selecting the perfect truck for the job.

#### FE**180** GAS 2021 and 2020 SINGLE 5 17.995 / 25.710 6.390 / 12.700 11 855 133.9" (E) 151.6" (G) 169.3" (H) 187.0" (K) 228.5" 246.3" 264.0" 281.7" 92.8" 85 21 104.9" 122.6" 140.3" 158.0" 12' to 20' (22' with FUSO review) FUSO PSI-GMPT, V8, 6.0L Gasoline Gasoline 6.0L (365 in<sup>3</sup>) 297 361 Standard CNG and LPG capable in future models (option) 40 / In-rail aft-axle Allison 1000 Series™ 6-speed automatic, torque converter with lockup clutch Electronic, closed-loop with adaptive shift mapping Torque converter turbine-driven spur gear (option) Dash-mounted Standard C-channel, straight 7.08 56.565 400.410 35.8 / 33.5 Standard Standard 6,835 / 13,230 Single-reduction hypoid 5.714 Option Laminated leaf springs Single front, dual rear 225/70R19.5 14PR LR:G hwy front / traction rear 19.5" x 6.75" /6-lug Single-caliper discs, vacuum/hydraulic Drum/driveline, internal expanding shoe 4-Channel Integral hydraulic boost Tilt & telescoping 42.6, 47.6, 52.6, 57.6 Maintenance-free / 1125 CCA 180 Option Standard Standard Standard Standard Standard Option

### **OPTIONS TO FIT YOUR IMAGE.**

Image is important. So is a cab with a quality paint finish that's durable. Choose from six cab colors, all developed to deliver a polished, professional appearance that fits your business and applications.

#### CAB COLOR

NATURAL WHITE

Accuracy of indicated hues is limited by paper/electronic reproduction.

#### **FABRIC STYLE**

#### **OPTIONAL FEATURES:**

- · Mobileye Collision Avoidance System
- · Clarion AM/FM Radio with hands-free Bluetooth®
- · Roof Air Deflector
- · Heated Mirrors

- · Chrome Trim Package
- · Floor Mats
- · Limited-Slip Differential (LSD)
- · PTO Capability for Allison Transmission
- · Wheel Simulators

## SUPERIOR SERVICE. GUARANTEED FOR THE LIFE OF YOUR TRUCK.

Count on us for parts and support you need to keep your FUSO truck operating at peak performance. We'll be here for you, and that's a promise.

#### **FUSO**FIRST™ MAKES YOUR UPTIME OUR PRIORITY.

Each FE GAS truck comes standard with our FUSOFirst comprehensive owner support program. It includes 24/7 roadside assistance, a web-friendly mobile app, plus access to owner/operator training and education.

#### WARRANTY COVERAGE THAT PROTECTS YOUR INVESTMENT.

FUSO protects your new FE investment with a generous warranty package<sup>†</sup>. This package combines 3-year/36,000 mile bumper-to-bumper, 5-year frame coverage, and 5-year/75,000-mile powertrain limited warranties into one strong standard warranty.

In addition, the package includes a 2-year extension to the standard 3-year Allison transmission<sup>††</sup> warranty as a free standard. The truck's transmission is now covered by a 5-year/unlimited mileage warranty. See your local certified Allison Transmission Service Center for more details.

† Please see your local dealer for details and warranty limitations.

†† Allison Transmissions are warranted separately by Allison and work is performed by Allison's authorized sales and service locations.

Please note: Changes may have been made to the product since this publication went to press (08/2019). FUSO reserves the right to make changes to the information, design and specification without notice. The illustrations may show accessories and items of special equipment which are not part of standard specification. This brochure may contain models and services which are not available in certain countries. For the most current information, availability and pricing, please contact your nearest authorized FUSO truck dealership.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. Chassis-cab dimensions, weights are +/- 3%.